

136 to 174 MHz, 3 dBi Folded Dipole Antenna with N Female, Vertical Polarization, 1 Port, 1.5 VSWR

KP-138SPFD-3-NF



Features

- Frequency coverage for 136 MHz to 174 MHz with Type N Female connector and gain 3 dBi / 0.85 dBd antenna
- Multiple Folded dipoles can be mouted on a mast for best performance
- Feild adjustable radition patterns with 100W max input power per port
- Easy and quick time to installations with U-Bolt mounts
- Industrially tuned folded dipole allows plug and play
- Weather and corrsion free made of high-grade aluminum alloys
- Vertical Polarization

Applications

- Outdoor point-to-point (PtP) or point-to-multipoint (PtMP) applications
- VHF radio applications supported with Trunking for two-way radio communications
- Public Safety / Emergency services / Marine communications / Rail road communications
- Tetra and P-25 Applications exclusively supported
- Land Mobile Radio (LMR) and Private Mobile Radio (PMR)
- Fixed and mobile services for paging/voice/data in full duplex and half duplex mode

Description

The KP Performance KP-138SPFD-3-NF 136 to 174 MHz, 3 dBi folded dipole antenna, with N female connector is a low cost, high performance antenna designed for high power applications. With a frequency range of 136 to 174 MHz, this folded dipole antenna is suitable for military communications, trunking, public safety, industrial communication, and amateur radio applications. The folded dipole antenna's beamwidth can be adjusted according to applications by fixing dipoles at certain heights and directions. This high gain 3 dBi antenna transmits high power signals, increasing the signal strength, thus providing improved coverage, better broadcast control, and faster speed.

KP's KP-138SPFD-3-NF folded dipole antenna is a dipole stand-alone made of aluminum alloy, and thus packaging, transportation, and installation become easier. It has a 1.5 VSWR that results in the best power transfer and reduced losses. This 136 to 174 MHz VHF/UHF antenna is one of the simplest and most widely used antenna producing radiation patterns as that of an electric dipole. It comes with a threaded and weatherproof N female connector type which ensures a reliable physical connection and can be fixed on a pole using the U-bolt brackets that come with the antenna.

This folded dipole antenna uses vertical polarization to transmit signals, thus reducing interference and performing better at lower heights. Our folded dipole antenna has 1 port to connect an external circuit with 100W maximum input power per port. All components of this 3 dBi antenna are DC grounded for lightning protection, have a rugged outdoor design, and have a high-power handling capacity.

This antenna with a 3 dBi maximum gain is ideal for LMR, military, airports, construction, mining, commercial applications and radio users. This KP-138SPFD-3-NF folded dipole antenna from KP comes in compact packaging for lower shipping costs, is in stock and available for same-day shipping. For further information on similar products, our expert technical support and highly trained sales team can get you the perfect 136 to 174 MHz, 3 dBi folded dipole antenna with a N female connector as per your requirement.

Configuration

Band Type	Single
Radiation Pattern	Omni Directional
Polarization	Vertical
Connector Type	N Female
Number of Ports	1

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[136 to 174 MHz, 3 dBi Folded Dipole Antenna with N Female, Vertical Polarization, 1 Port, 1.5 VSWR KP-138SPFD-3-NF](#)

136 to 174 MHz, 3 dBi Folded Dipole Antenna with N Female, Vertical Polarization, 1 Port, 1.5 VSWR

KP-138SPFD-3-NF



Lightning Protection

DC Ground

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	136		174	MHz
Input VSWR			1.5:1	
Impedance		50		Ohms
Gain			3	dBi
Input Power			100	Watts

Mechanical Specifications

Radome Material	Aluminum Alloy
Size	
Length	35.9 in [911.86 mm]
Width	40.6 in [103.12 cm]
Height	1.3 in [33.02 mm]
Weight	2.64 lbs [1.2 kg]

Environmental Specifications

Temperature	
Operating Range	-40 to +80 deg C

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[136 to 174 MHz, 3 dBi Folded Dipole Antenna with N Female, Vertical Polarization, 1 Port, 1.5 VSWR KP-138SPFD-3-NF](#)

136 to 174 MHz, 3 dBi Folded Dipole Antenna with N Female, Vertical Polarization, 1 Port, 1.5 VSWR

KP-138SPFD-3-NF



Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [136 to 174 MHz, 3 dBi Folded Dipole Antenna with N Female, Vertical Polarization, 1 Port, 1.5 VSWR KP-138SPFD-3-NF](#)

URL:

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.

KP-138SPFD-3-NF CAD Drawing

