

## KP-5PDA-EPMP13L

### Cambium®: ePMP1000™, ePMP3000L™, Force 300CSM™ Quick-Connect Adapter for 5GHz ProLine Parabolic and Horn

- Simplified installation with quick-connect waveguide technology and weatherproof snap-in adapter designed specifically for the Cambium® ePMP1000™, ePMP3000L™, Force 300CSM™
- Used with KP's 1ft and 2ft 5 GHz ProLine Parabolic and Horn Antennas to mitigate interference and improves signal strength in PTP and PTMP applications
- Adjustable horizontal/vertical or  $\pm 45^\circ$  polarization



### Specifications

RF connection	Quick-Connect Waveguide
Frequency	4.9 – 6.4 GHz
Return Loss	14 typ   12 max
VSWR	1.5 typ   1.7 max
Port Isolation	30 dB typ   25 dB max
Compatible Radios	Cambium® ePMP1000™, ePMP3000L™, Force 300CSM™
Compatible Antennas	KP® 5 GHz ProLine Parabolics and Horns
Wind Velocity, Survival	201 km/h   125 mph
Temperature Range	-40° to +60° C   -40° to +140° F
Net Weight	0.23 kg   0.5 lbs
Adapter Dimensions	113 x 144 x 126 mm   4.4 x 5.7 x 5.0 in

