

617-7125 MHz, 2-5 dBi Gain, Omni-directional Antenna with Magnetic NMO Mount, N-Female Connector

KPANMOB1002-NF



Features

- · Outdoor Rated Omni Directional Antenna
- 2-5 dBi Gair
- Easy to install magnetic mount offering temporary plug and play installation

Applications

 Infotainment systems, Routers, Wi-Fi hotspots, HD video transmission, Gateways, Dash cameras, Public transportation Public Safety Networks

- · NMO Magnetic Mount, Black ABS Radome
- 2.5:1 VSWR Max
- · 10 Foot, Black Low-Loss LMR195 Equivalent
- · N-Female Connector
- Connected cars or self driving cars, Fleet management, Logistics
- · IoT, Industrial IoT, Zigbee, Bluetooth, Wi-Fi

Description

The KP Performance KPANMOB1002-NF is an omnidirectional antenna with a magnetic NMO mount specifically designed for high-performance applications. Our high-quality antenna can operate at frequencies ranging from 617 to 7125 MHz, which is ideal for indoor low-profile, in-building, and mobile applications. This non-infrastructure antenna has a 5 dBi gain, which transmits high-power signals and faster speed. This vertically polarized omni antenna with NMO mount is available in black color.

The KPANMOB1002-NF in-building antenna from KP Performance features an NMO-type magnetic mount, which is ideal when the portability of the antenna is required. Our magnetic mount comes with an N-type female connector and can be used for WLAN, Wi-Fi, public safety, and mobile RF applications. This NMO antenna mount is constructed with a heavy-duty magnet to ensure secure mounting. No drilling is required for the installation of this antenna mount, making it easy to fine-tune the antenna location. The magnetic base is easy to install and offers a temporary plug-and-play installation.

KP Performance has one of the largest in-stock selection of omnidirectional antennas with same-day shipment. Use our on-line ordering system to purchase your KPANMOB1002-NF antenna 24 hours a day with same-day shipping and no MOQs (minimum order quantities). For further information on similar products, our expert technical support and knowledgeable sales team can help you get the ideal vertically polarized antenna with a magnetic NMO mount for your requirements.


Configuration

Design Band Type Radiation Pattern Polarization Connector Type Number of Ports Omni Single Omni Directional Vertical N Female

Electrical Specifications

	ypical Maximum	Minimum	Description
MHz	7,125	617	Frequency Range
	1.5:1		Frequency Range Input VSWR
dBi	5	2	Gain
Watts	100		Input Power
		2	Gain Input Power

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 617-7125 MHz, 2-5 dBi Gain, Omni-directional Antenna with Magnetic NMO Mount, N-Female Connector KPANMOB1002-NF





617-7125 MHz, 2-5 dBi Gain, Omni-directional Antenna with Magnetic NMO Mount, N-Female Connector

KPANMOB1002-NF



Mechanical Specifications

Size

 Length
 4.95 in [125.73 mm]

 Width
 3 in [76.2 mm]

 Height
 3 in [76.2 mm]

 Weight
 1.25 lbs [566.99 g]

Environmental Specifications

Plotted and Other Data

Notes:

Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 617-7125 MHz, 2-5 dBi Gain, Omni-directional Antenna with Magnetic NMO Mount, N-Female Connector KPANMOB1002-NF

 $\label{lem:url:moment} \textbf{URL:} \ \textbf{https://www.kpperformance.com/} 617-7125-mhz-2-5-dbi-gain-omni-directional-antenna-with-magnetic-nmo-mount-n-female-connector-kpanmob1002-nf-p.aspx$

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the

suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.

KPANMOB1002-NF CAD Drawing

