

## 3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole, SMA Male Connector, 4.5 dBi Gain

### KPANRBD1052



#### Features

- 3300-3800 MHz, 4.5 dBi Gain
- SMA male connector
- Plug and play
- VSWR < 2:1
- Vertical polarization
- Dipole antenna

#### Applications

- CBRS application range
- WISP applications
- 5G wireless network
- Remote monitoring
- Telemedicine, disaster response
- RFID
- Surveillance systems
- Broadcasting equipment addition
- 5G bands: n48, n77, n78
- 4G LTE bands: B22, B42, B43, B48, B49, B52

#### Description

The KP performance KPANRBD1052 is a 3.3 GHz to 3.8 GHz blade style antenna that is ideal for CBRS application range, WISP, 5G wireless network, remote monitoring, telemedicine, disaster response, RFID, surveillance systems and broadcasting equipment applications. This communication antenna has a black radome made from ABS material. Our antenna is 0.86 inches wide, 8.19 inches long and 0.51 inches tall.

These omni antennas have a waterproof design, vertical polarization and a SMA type male connector. This KPANRBD1052 antenna transmits high-power signals, increasing the signal strength, thus providing improved coverage, better-broadcast control and faster speed. KP performance dipole antenna has a gain of 4.5 dBi for the 3.3 GHz to 3.8 GHz frequency range. Our black colored omnidirectional antenna functions between -20 to 65 degrees C and has 50 ohms impedance.

The SMA male connector on the communication antenna enables it to be used vertically. KP Performance 4.5 dBi antennas have a sturdy outdoor design, a high power handling capacity, and all of their components are DC grounded for lightning safety. Our high-quality KPANRBD1052 omnidirectional antenna has a maximum input VSWR of 2:1, which results in the best power transfer and reduced losses.

The KP performance has one of the largest in-stock collections of 4.5 dBi gain omni directional antennas for all your critical equipment and power sources. Quickly make your online purchase right now to take advantage of our same-day shipping. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the 3.3 GHz to 3.8 GHz blade style antenna as per your requirements.

#### Configuration

Design	Rubber Duck
Band Type	Single
Radiation Pattern	Omni Directional
Polarization	Vertical
Connector Type	SMA Male

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	3,300		3,800	MHz
Input VSWR			2:1	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole, SMA Male Connector, 4.5 dBi Gain KPANRBD1052](#)

3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole,  
 SMA Male Connector, 4.5 dBi Gain

**KPANRBD1052**



Impedance	50	Ohms
Gain	4.5	dBi
Input Power	10	Watts

**Mechanical Specifications**

Radome Material	ABS
<b>Size</b>	
Length	8.19 in [208.03 mm]
Width	0.86 in [21.84 mm]
Height	0.51 in [12.95 mm]
Weight	0.05544 lbs [25.15 g]

**Environmental Specifications**

<b>Temperature</b>	
Operating Range	-20 to +65 deg C
Storage Range	-20 to +65 deg C

**Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole, SMA Male Connector, 4.5 dBi Gain KPANRBD1052](#)

3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole,  
SMA Male Connector, 4.5 dBi Gain

**KPANRBD1052**



## Appendix

**Electrical Downtilt:** Angle in the antenna's elevation pattern in which the maximum gain occurs.

**Gain:** Antenna's average gain.

**Front to Back Ratio @ 180°±30°:** Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

**Cross-polarization Ratio (dB):** Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole, SMA Male Connector, 4.5 dBi Gain KPANRBD1052](https://www.kpperformance.com/3300-mhz-to-3800-mhz-antenna-sma-male-connector-4.5-dbi-gain-kpanrbd1052-p.aspx)

URL: <https://www.kpperformance.com/3300-mhz-to-3800-mhz-antenna-sma-male-connector-4.5-dbi-gain-kpanrbd1052-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.

# 3.3 GHz to 3.8 GHz Blade Style Antenna, Dipole, SMA Male Connector, 4.5 dBi Gain

## KPANRBD1052 CAD Drawing

